

ReacProc: A Tool to Process Reactions Describing Particle Interactions

Andrey Siver*

1st February 2008

Contents

1	Introduction	1
2	Data structures	2
3	Description of the basic functions	3
4	Appendix A. The grammar of reactions	4
5	Acknowledgments	5

Abstract

ReacProc is a program written in C/C++ programming language which can be used (1) to check out of reactions describing particles interactions against conservation laws and (2) to reduce input reaction into some canonical form. Table with particles properties is available within ReacProc package.

1 Introduction

ReacProc can be used (1) to check out of reactions describing particles interactions against conservation laws (for example, for electric charge) and (2) to reduce input reaction into some canonical form.

The followings functionalities were realized:

1. Parsing of reaction. It means reading reaction from a stream and building corresponding dynamical structure of connection lists. Also reaction syntax is validating against some grammar (see section 4);
2. Reducing of grouping brackets (see section 3);
3. Particle synonyms processing (see section 3);
4. Sorting of particle and particle groups in reaction (according to an order in a dictionary) (see section 3);
5. Checking conservation laws and printing messages if it's needed (see section 3);
6. Print reaction to output stream from corresponding data structure (see section 3).

*IHEP

We use PDDL notation [Alekhin and et al. 1987b,Alekhin and et al. (1987a)] for reaction.

Reducing to a canonical form means applying 1, 2, 3, 4, 6 functionalities correspondingly.

ReacProc is written in C/C++ programming language and uses Bison[Donnelly and Stallman 2002]+Flex[Paxson 1995] parser generator.

In order to check conservation laws we need some table with particle properties. This file was created from publicly available Particle Data Group file and contains following particle properties: electric charge, barion number, S-, C-, B-, T-quantum numbers. There was also created file with lepton quantum numbers. ReacProc can check conservation laws corresponding to all of these properties. There is also file containing a dictionary.

To run ReacProc one do call corresponding executable with input file. ReacProc reads line by line and process strings ending with ";". "\"" symbol is considered as line continuation character (multi-lines can be written with it). During processing ReacProc creates several files:

- "rp-accept.txt" contains reactions satisfying tested conservation laws (in "rp-accept-s.txt" reactions are sorted);
- "rp-reject.txt" contains reactions which do not satisfy tested conservation laws (in "rp-reject-s.txt" reactions are sorted);
- "rp-unknown.txt" contains reactions which cannot be processed by ReacProc;
- "rp-log.txt" contains debug messages and additional information about processed reactions.

Another kind of usage ReacProc (and perhaps more powerful) is usage it as a module in another system (for example, in specialized databases). So it's important to describe general structure of ReacProc. The rest of the paper is devoted to this point.

As an example of application let's call possible program for building mathematical observables from corresponding reactions (which in their order can be used in some calculations).

ReacProc available here <http://sirius.ihep.su/~siver/rp.zip>

2 Data structures

The most important data structure is called 'f_s'. Here is its definition written in C programming language:

```
struct f_s {
struct f_s *l;
struct f_s *r;
int c;
char *n;
struct gf_s *deca;
}
```

, where the fields means: 'l','r' - pointers to abstract left and right (or previous and next) 'f_s' elements, 'n' - pointer to name of particle, 'c' - counter of particles, 'deca' - pointer to decay description of particle. So, this structure is for one type of particle appearing in reaction. But since it can be connected with others such structure, any reference to this structure will be reference to the group of particles structures.

'gf_s' data type is defined this way:

```
struct gf_s {
struct gf_s *l;
struct gf_s *r;
struct f_s *pg;
int sign;
}
```

, where the fields means: 'l','r' - pointers to abstract left and right (or previous and next) 'gf_s' elements, 'pg' - reference to particle group, 'sign' - unary sign which prescribing to 'pg' group.

Full reaction is represented as following:

```
struct reac {
struct f_s *is;
struct gf_s *fs;
}
```

, where 'is' field stands for initial state (sequence of particles types, ordinary in amount of two or one), 'fs' field stands for final state (sequence of groups of particle sequences).

3 Description of the basic functions

Let's describe most important functions and global variables which they use.

- The parsing function:

```
int yyparse(void);
```

Description: this function is generated by Bison. It calls 'yylex' function which in its order reads reaction from 'yyin' stream. After call 'yyparse' reaction will be in 'r' global variable.

- The canonization function:

```
struct reac* canoni(reac* r);
```

Description: it transforms reaction 'r' into the canonical form. It calls 'syn_proc_gf_s', 'reduce_gf_s' and 'sort_full_gf_s' functions.

- The particle synonyms processing function:

```
f_s* syn_proc_gf_s(f_s*);
```

Description: it replaces synonym of particle by the key synonym (which actually is PDG name) which stands at first place in synonyms list of the dictionary file;

- The function for round brackets (named "grouping") reduction:

```
gf_s* reduce_gf_s(gf_s*);
```

Description: it reduces parenthesis. For example, expression '(E+ + MU+) X' is equal to 'E+ X + MU+ X'. Expression with grouping brackets is represented as "generalized" particle with 'n' and 'c' fields equaling to "?compo" and 0 correspondingly;

- The sorting function:

```
gf_s* sort_full_gf_s(gf_s*);
```

Description: it sorts according to 'ord_full_gf_s' and at the lowest level - 'ord(char*,char*)' function which has two ordering modes: lexicographical (in case a global 'ord_type' = 'ORD_TRUE_LEX') that is order that every English dictionary has, and so called dictionary order (in case the global 'ord_type' = 'ORD_DICT') that is order of some particle dictionary (ReacProc uses 'dict-syn.txt' file as a particle dictionary by default). These modes have advantages in certain situations: while ORD_TRUE_LEX mode is useful when we compare reactions, with ORD_DICT mode sorting is more logical and physical well founded (see example below);

- The function checking conservation law:

```
int test_reac(reac *r, const char s[], prop *pp, int kolvo);
```

Description: it tests reaction 'r' against law naming 's' and property table 'pp' with 'kolvo' elements. It return '0' if no error was detected and some signal (such as RP_SIGN_P_UNK) otherwise. It uses global variable 'SIGN_conser' which assigns the type of conservation law (0 for equality, -1 and 1 for '<=' and '>=' equality respectively).

- The output function:

```
void out_to(FILE *f, reac* s);
```

Description: it prints reaction 's' into stream 'f'. It uses 'out_f_s' and 'out_gf_s' functions.

Let's write a reaction and see how it's represented.

```
E+ E- --> W- < QUARK QUARKBAR > W+ < TAU+ NUTAU + MU+ NUMU + E+ NUE >
```

, where brackets denote sub-decays processes. Using the labels (Ax, Bx, Cx, Dx, Ex) instead of memory pointers memory structure corresponding to the reaction can be shown by following ('->' sign shows value of the variables and '-->' shows value of the references)

```
L1: reaction ( is -> I1 , fs -> F1 );

I1: f_s ( 1 -> NULL , r -> I2 , c -> 1 , n --> "E+" , deca -> NULL);
I2: f_s ( 1 -> I1 , r -> NULL , c -> 1 , n --> "E-" , deca -> NULL);
F1: gf_s ( 1 -> NULL , r -> NULL , pg -> F2 , sign -> +1 );
F2: f_s ( 1 -> NULL , r -> F3 , c -> 1 , n --> "W-" , deca -> A1);
F3: f_s ( 1 -> F2 , r -> NULL , c -> 1 , n --> "W+" , deca -> B1);
A1: gf_s ( 1 -> NULL , r -> NULL , pg -> A2 , sign -> +1 );
A2: f_s ( 1 -> NULL , r -> A3 , c -> 1 , n --> "QUARK" , deca -> NULL);
A3: f_s ( 1 -> A2 , r -> NULL , c -> 1 , n --> "QUARKBAR" , deca -> NULL);
B1: gf_s ( 1 -> NULL , r -> B2 , pg -> C1 , sign -> +1 );
B2: gf_s ( 1 -> NULL , r -> B3 , pg -> D1 , sign -> +1 );
B3: gf_s ( 1 -> B2 , r -> NULL , pg -> E1 , sign -> +1 );
C1: f_s ( 1 -> NULL , r -> C2 , c -> 1 , n --> "TAU+" , deca -> NULL);
C2: f_s ( 1 -> C1 , r -> NULL , c -> 1 , n --> "NUTAU" , deca -> NULL);
D1: f_s ( 1 -> NULL , r -> D2 , c -> 1 , n --> "MU+" , deca -> NULL);
D1: f_s ( 1 -> D1 , r -> NULL , c -> 1 , n --> "MUTAU" , deca -> NULL);
E1: f_s ( 1 -> NULL , r -> E2 , c -> 1 , n --> "E+" , deca -> NULL);
E2: f_s ( 1 -> E1 , r -> NULL , c -> 1 , n --> "NUE" , deca -> NULL);
```

After canonization in the case of 'ord_type=ORD_TRUE_LEX' the reaction has following form :

```
e+ e- --> W+ < e+ nu(e) + mu+ nu(mu) + nu(tau) tau+ > W- < QUARK QUARKBAR > ;
```

and in the case of 'ord_type=ORD_DICT':

```
e+ e- --> W+ < e+ nu(e) + mu+ nu(mu) + tau+ nu(tau) > W- < QUARK QUARKBAR > ;
```

(notice order of 'tau+' and 'nu(tau)').

4 Appendix A. The grammar of reactions

This appendix contains reactions grammar using in ReacProc. Entry point is 'reaction'. It was cut out from corresponding Bison *.y file.

```

reaction : initial_state ARROW final_state END
|
    error END
;
initial_state : beam target
;
beam : PARTICLE
;
target : /* empty */
| PARTICLE target
;
particle : PARTICLE
| PARTICLE LC final state RC
| LP final state RP
;
decay_group : /* Empty */ // d._g. has type f_s
| particle decay_group
;
final_state : decay_group // f.s. has type gf_s
| decay_group PLUS final state
| decay_group MINUS final state
| final state PLUS CC

```

Terminal elements (such as ARROW, END and etc) are described below. This Flex code was cut out from corresponding *.lex file:

```

"-->" return(ARROW);
";" return(END);
"(" return(LP);
")" return(RP);
"<" return(LC);
">" return(RC);
"+" return(PLUS);
"-" return(MINUS);
"CC" return(CC);
[ \t\n\r]+ ; /* Do nothing */
[A-Za-z\+\-\:\\".\*\=\%\_\(\)0-9\|]+ return(PARTICLE);

```

5 Acknowledgments

Author would like to thank Zenin O. V., Ezhela V. V.

The work was **not** supported by the project RFFI-05-07-90191-w.

References

- ALEKHIN, S. I. and ET AL., 1987a: *Particle Physics Data System at IHEP. Data Description Language. IHEP-REPORTS-87-161.*
- ALEKHIN, S. I. and ET AL., 1987b: *PPDS COMPAS Primer. IHEP-REPORTS-87-125.*
- DONNELLY, Charles and Richard STALLMAN, Feb 2002: *Bison. The YACC-compatible Parser Generator.*
 URL <http://www.gnu.org/software/bison/bison.html>

PAXSON, Vern, Mar 1995: *Flex (version 2.5). A fast scanner generator.*
URL <http://www.gnu.org/software/flex/>